



# CROWN CONTRACT

## TECHNICAL DATA SHEET

### **CROWN CONTRACT VINYL MATT**

Crown Contract Vinyl Matt is a smooth trade quality emulsion with excellent coverage and a beautiful even appearance on interior walls and ceilings. Easy to apply and fast drying, Crown Contract Vinyl Matt provides a flat modern non-reflective look and offers approximate cover of 16m<sup>2</sup> per litre.

### **AVAILABILITY**

<b>Colour range</b>	Brilliant White & Magnolia
<b>Packaging</b>	5 litres

### **PROPERTIES**

<b>Drying time</b>	Under normal drying conditions touch dry in 2 hours, recoatable after 4 hours. Allow for adequate ventilation during the drying period.
<b>Finish</b>	Matt.
<b>Composition</b>	Pigment: Titanium Dioxide, coloured pigments and extenders Binder: Vinyl Acetate Copolymer Solvent/Thinner: Water
<b>Spreading rate</b>	Up to 16m <sup>2</sup> per litre depending on surface texture.
<b>Wet film thickness</b>	62 micrometres at 16m <sup>2</sup> per litre.
<b>Dry film thickness</b>	18.7 micrometres at 16m <sup>2</sup> per litre
<b>Volume solids</b>	30% White other colours will vary
<b>VOC content</b>	EU limit value for this product (cat.A/d): 30 g/l (2010) This product contains max. 2 g/l VOC.
<b>Limitations</b>	For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

### **PREPARATION**

<b>New surfaces</b>	All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed and stabilised. Porous surfaces should be 'mist' coated with Crown Contract Matt thinned with up to 40% clean water.
<b>COATING SYSTEM</b>	Apply two coats
<b>APPLICATION</b>	Stir well before use. Apply by brush or roller. For airless spray (dilution may be required). For further information contact the Customer Relations Team

<b>CLEANING</b>	Return surplus material to container. Wash with clean water immediately after use.
<b>HEALTH AND SAFETY</b>	
Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact our Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.	
<b>GENERAL INFORMATION</b>	
<u>New surfaces</u>	
	All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed and stabilised. Porous surfaces should be 'mist' coated with Crown Contract Matt thinned with up to 40% clean water.
<u>New surfaces</u>	
	All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed and stabilised. Porous surfaces should be 'mist' coated with Crown Contract Matt thinned with up to 40% clean water.
Apply all products in accordance with BS 6150: Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.	
Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints are unable to guarantee results as it has no control over the conditions under which its products are applied. For help or more information contact the Customer Relations Team on 0330 0240281. Before using this product please ensure you have the latest information.	
The information is correct at date of issue May 2015	