



TECHNICAL DATA SHEET

CROWN CONTRACT MATT FOR CONTRACT WORK

Contract Matt emulsion offers fantastic coverage, with a breathable finish. It's perfect for use on new plaster, allowing surfaces to dry through. Low spatter formulation reduces mess during application. This good quality, yet economical emulsion offers coverage of approximately 13 m² per litre

AVAILABILITY

Colour range Brilliant White & Magnolia

Packaging 10 litres

PROPERTIES

Drying time Under normal drying conditions touch dry in 2 hours, recoatable after 4 hours. Allow for adequate ventilation during the drying period.

Finish Matt.

Composition
 Pigment: Titanium Dioxide, coloured pigments and extenders
 Binder: Vinyl Acetate Copolymer
 Solvent/Thinner: Water

Spreading rate Up to 13m² per litre depending on surface texture.

Wet film thickness 77 micrometres at 13m² per litre.

Dry film thickness 18 micrometres at 13m² per litre

Volume solids 24% White other colours will vary

VOC content EU limit value for this product (cat.A/d): 30 g/l (2010)
 This product contains max. 2 g/l VOC.

Limitations For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

PREPARATION

New surfaces

All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed and stabilised. Porous surfaces should be 'mist' coated with Crown Contract Matt thinned with up to 40% clean water.

COATING SYSTEM Apply two coats

APPLICATION Stir well before use. Apply by good quality brush or roller. For airless spray (dilution may be required). For further information contact the Customer Relations Team

CLEANING	Return surplus material to container. Wash with clean water immediately after use.
HEALTH AND SAFETY	
<p>Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact our Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.</p>	
GENERAL INFORMATION	
<p>Apply all products in accordance with BS 6150: Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.</p> <p>Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints are unable to guarantee results as it has no control over the conditions under which its products are applied. For help or more information contact the Customer Relations Team on 0330 0240281 . Before using this product please ensure you have the latest information.</p> <p>The information is correct at date of issue May 2015</p>	