



TECHNICAL DATA SHEET

CROWN CONTRACT VINYL SILK	
Crown Contract Vinyl Silk is easy to apply and durable with a wipeable high sheen finish, suitable for interior walls and ceilings.	
AVAILABILITY	
Colour range	Brilliant White & Magnolia
Packaging	2.5 litres and 5 litres
PROPERTIES	
Drying time	Under normal drying conditions touch dry in 2-3 hours, recoatable after 4 hours. Allow for adequate ventilation during the drying period.
Finish	Silk.
Composition	Pigment: Titanium dioxide, coloured pigments and extenders. Binder: VA Copolymer Solvent: Water
Spreading rate	Up to 15m ² per litre depending on surface texture.
Wet film thickness	66.6 micrometres at 15m ² per litre.
Dry film thickness	20 micrometres at 15m ² per litre
Volume solids	30 % White other colours will vary
VOC content	EU limit value for this product (cat.A/b): 100 g/l (2010) This product contains max. 1 g/l VOC.
Limitations	For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.
PREPARATION	
New surfaces	
	All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed and stabilised. Porous surfaces should be 'mist' coated with Crown Contract Vinyl Silk thinned with up to 40% clean water.
Previously decorated surfaces	
	All surfaces must be suitably dry, and free from anything that will interfere with the adhesion of the materials to be applied eg dirt, grease etc. Remove all loose, and failing or suspect paint. Remove grey and denatured surfaces by rubbing down with abrasive paper. Feather edges of sound paint. Remove all dust. Organic growth must be removed and the areas treated with a suitable Fungicidal Solution. Fill any fixing holes, cracks and shallow surface defects with a Ready Mixed Filler. Patch prime bare and filled areas with a Stain Block Primer. Wash remaining sound paint with hot water and liquid detergent solution to remove any

	contaminants, frequently changing the water. Any glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues. Allow to dry. If after cleaning, any areas are still contaminated with substances likely to cause staining and/or bleeding, patch prime with one coat of Stain Block Primer. Bring forward patch primed areas with one coat of Crown Contract Vinyl Silk.
COATING SYSTEM	Apply two coats
APPLICATION	Stir well before use. Apply by good quality brush or roller. For airless spray (dilution may be required). For further information contact the Customer Relations Team
CLEANING	Return surplus material to container. Wash with clean water immediately after use.
HEALTH AND SAFETY	
<p>Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact our Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.</p>	
GENERAL INFORMATION	
<p>Apply all products in accordance with BS 6150: Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.</p> <p>Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints are unable to guarantee results as it has no control over the conditions under which its products are applied. For help or more information contact the Customer Relations Team on 0330 0240281. Before using this product please ensure you have the latest information.</p> <p>The information is correct at date of issue May 2017.</p>	